

14C7

GRID-No.2 VOLTAGE.	100 max.	volts
GRID-No.1 (CONTROL-GRID) VOLTAGE:		
Positive-bias value.	0 max.	volts
GRID-No.2 INPUT.	0.1 max.	watt
PLATE DISSIPATION.	1 max.	watt
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode. .	90 max.	volts
Heater positive with respect to cathode. .	90 max.	volts

- ▲ Nominal voltage = 14 volts.
- Nominal current = 0.16 ampere.
- ★ With external shield JEDEC No.308 connected to cathode.
- ◆ Greater than 1 megohm.

14F7

High-Mu Twin Triode

The 14F7 is the same as the 7F7 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	12.6 [▲]	volts
Current at 12.6 volts.	0.15 [●]	amp

14F8

Medium-Mu Twin Triode

The 14F8 is the same as the 7F8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	12.6 [▲]	volts
Current at 12.6 volts.	0.15 [●]	amp

- ▲ Nominal voltage = 14 volts.
- Nominal current = 0.16 ampere.

