



6677

# 6677/6CL6 POWER PENTODE

9-PIN MINIATURE TYPE

*For use in mobile communications equipment***GENERAL DATA****Electrical:**

Heater, for Unipotential Cathode:

Voltage. . . . .  $6.3 \pm 20\%$  . . . . . ac or dc volts

Current at 6.3 volts . . . . . 0.65 . . . . . amp

Direct Interelectrode Capacitances:<sup>o</sup>Grid No.1 to plate . . . . . 0.12 max.  $\mu\text{f}$ Grid No.1 to cathode, grid No.3 & internal shield, grid No.2, and heater. . . . . 11  $\mu\text{f}$ Plate to cathode, grid No.3 & internal shield, grid No.2, and heater. . . . . 5.5  $\mu\text{f}$ **Mechanical:**

Operating Position . . . . . Any

Maximum Overall Length . . . . . 2-5/8"

Maximum Seated Length. . . . . 2-3/8"

Length, Base Seat to Bulb Top (Excluding tip) . . . . .  $2" \pm 3/32"$ 

Diameter . . . . . 0.750" to 0.875"

Dimensional Outline. . . . . *See General Section*

Bulb . . . . . T6-1/2

Base . . . . . Small-Button Noval 9-Pin (JEDEC No.E9-1)

Basing Designation for BOTTOM VIEW . . . . . .9BV

Pin 1 - Cathode  
Pin 2 - Grid No.1  
Pin 3 - Grid No.2  
Pin 4 - Heater  
Pin 5 - Heater  
Pin 6 - Plate



Pin 7 - Grid No.3,  
Internal  
Shield  
Pin 8 - Grid No.2  
Pin 9 - Grid No.1

**AMPLIFIER — Class A<sub>1</sub>****Maximum Ratings, Design-Maximum Values:**

PLATE VOLTAGE. . . . . 330 max. volts

GRID-No.3 (SUPPRESSOR-GRID) VOLTAGE. . . . . 0 max. volts

GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE . . . . . 330 max. volts

GRID-No.2 VOLTAGE. . . . . *See Grid-No.2 Input Rating Chart at front of Receiving Tube Section*

GRID-No.1 (CONTROL-GRID) VOLTAGE:

Negative-bias value. . . . . 50 max. volts

Positive-bias value. . . . . 0 max. volts

GRID-No.2 INPUT:

For grid-No.2 voltages up to 165 volts . . . . . 2 max. watts

For grid-No.2 voltages between 165 and 330 volts. . . . . *See Grid-No.2 Input Rating Chart at front of Receiving Tube Section*

6677



# 6677/6CL6

## POWER PENTODE

PLATE DISSIPATION . . . . .	8.5 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode . . . . .	100 max.	volts
Heater positive with respect to cathode . . . . .	100 max.	volts
BULB TEMPERATURE (At hottest point on bulb surface) . . . . .	210 max.	°C

### Typical Operation and Characteristics:

Heater Voltage . . . . .	6.3	volts
Plate Voltage . . . . .	250	volts
Grid No.3 . . . . .	<i>Connected to cathode at socket</i>	
Grid-No.2 Voltage . . . . .	150	volts
Grid-No.1 Voltage . . . . .	-3	volts
Peak AF Grid-No.1 Voltage . . . . .	3	volts
Zero-Signal Plate Current . . . . .	30	ma
Max.-Signal Plate Current . . . . .	31	ma
Zero-Signal Grid-No.2 Current . . . . .	7	ma
Max.-Signal Grid-No.2 Current . . . . .	7.2	ma
Plate Resistance (Approx.) . . . . .	0.15	megohm
Transconductance . . . . .	11000	μmhos
Load Resistance . . . . .	7500	ohms
Total Harmonic Distortion . . . . .	8	%
Max.-Signal Power Output . . . . .	2.8	watts

### Maximum Circuit Values:

#### Grid-No.1-Circuit Resistance:

For fixed-bias operation . . . . .	0.1 max.	megohm
For cathode-bias operation . . . . .	0.5 max.	megohm

\* When the heater is operated from storage-battery-with-charger supply or similar supplies, the normal battery-voltage fluctuation may be as much as 35 per cent or more. Although such variation in heater voltage is permissible for short periods, reliability can be increased with improved supply-voltage regulation.

° Without external shield.

### SPECIAL RATINGS & PERFORMANCE DATA

#### Heater-Cycling Life Performance:

This test is performed on a sample lot of tubes from each production run. A minimum of 2000 cycles of intermittent operation is applied under the following conditions: heater volts = 7.5 cycled one minute on and one minute off, heater 135 volts positive with respect to cathode, and all other elements connected to ground. At the end of this test, tubes are checked for heater-cathode shorts and open circuits.

#### Transconductance at Reduced Heater Voltage:

Average Value . . . . .	8800	μmhos
With heater volts = 5, plate volts = 250, grid No.3 connected to cathode at socket, grid-No.2 volts = 150, and grid-No.1 volts = -3.		