

675



675

# FULL-WAVE HIGH-VACUUM RECTIFIER

RENEWAL TYPE FOR MAJESTIC RECEIVERS

| Heater                  | Coated Unipotential Cathode |                   |                  |
|-------------------------|-----------------------------|-------------------|------------------|
| Heater Arrangement      | <u>Series*</u>              | <u>Parallel**</u> |                  |
| Voltage                 | 12.6                        | 6.3               | a-c or d-c volts |
| Current                 | 0.4                         | 0.8               | amp.             |
| Maximum Overall Length  |                             |                   | 4-3/16"          |
| Maximum Seated Height   |                             |                   | 3-9/16"          |
| Maximum Diameter        |                             |                   | 1-9/16"          |
| Bulb                    |                             |                   | ST-12            |
| Base                    |                             |                   | Small 6-Pin      |
| Pin 1 - Heater, Mid-Tap |                             |                   | Pin 4 - Cathode  |
| Pin 2 - Heater          |                             |                   | Pin 5 - Plate #1 |
| Pin 3 - Plate #2        |                             |                   | Pin 6 - Heater   |



BOTTOM VIEW (5K)

## RECTIFIER

### *With Condenser-Input Filter:*

|                                   |                |
|-----------------------------------|----------------|
| A-C Plate Voltage per Plate (RMS) | 230 max. volts |
| D-C Output Current                | 60 max. ma.    |

- \* Heater voltage applied across the two sections in series between pins #2 and #6.
- \*\* Heater voltage applied across the two sections in parallel between pin #1 and pins #2 and #6 connected together.