

Medium-Mu Triode

NUVISTOR TYPE
For Industrial Applications

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	6.3 ± 10%	volts
Current at 6.3 volts	0.135	amp ←

Direct Interelectrode Capacitances
(Approx.):

Grid to plate	2.2	μf
Grid to cathode, shell, and heater . . .	4.2	μf
Plate to cathode, shell, and heater . . .	1.6	μf
Plate to cathode	0.26	μf
Heater to cathode	1.4	μf

Characteristics, Class A₁ Amplifier:


Plate Supply Voltage	-	-	75	volts
Plate Voltage	26.5	40	-	volts
Grid Supply Voltage	0	0	0	volts
Cathode Resistor	-	-	100	ohms
Amplification Factor	31	35	35	
Grid-Circuit Resistance	0.5	0.5	-	megohm
Plate Resistance (Approx.)	4400	3200	3000	ohms
Transconductance	7000	11000	11500	μmhos
Plate Current	2.8	6.8	10.5	ma
Grid Voltage (Approx.) for plate μa = 10.	-	-	-7	volts

Mechanical:

Operating PositionAny
Maximum Overall Length				0.800"
Maximum Seated Length				0.625"
Maximum Diameter				0.440"
Weight (Approx.)				1/15 oz ←
Envelope				Metal Shell MT4 ←
Socket	Cinch Mfg. Corp. No.133 65 10 001, or equivalent			
Base	Medium Ceramic-Wafer Twelvar 5-Pin (JEDEC No.E5-65)			
Basing Designation for BOTTOM VIEW				12AQ

Pin 1^a - Internal Connection—
Do Not Use

- Pin 2 - Plate
- Pin 3 - Same as Pin 1
- Pin 4 - Grid
- Pin 5 - Same as Pin 1
- Pin 6 - Same as Pin 1
- Pin 7 - Same as Pin 1
- Pin 8 - Cathode
- Pin 9 - Same as Pin 1
- Pin 10 - Heater
- Pin 12 - Heater



INDEX=LARGE LUG
●=PIN CUT OFF

← Indicates a change.



INDUSTRIAL SERVICE

Maximum Ratings, Absolute-Maximum Values:

For operation at any altitude

PLATE SUPPLY VOLTAGE.	330 max.	volts
PLATE VOLTAGE	110 max.	volts
GRID VOLTAGE:		
Negative-bias value	55 max.	volts
Peak-positive value	4 max.	volts
GRID CURRENT.	2 max.	ma
→ CATHODE CURRENT	15 max.	ma
PLATE DISSIPATION	1 max.	watt
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode .	100 max.	volts
Heater positive with respect to cathode .	100 max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:^b

For fixed-bias operation.	0.5 max.	megohm
For cathode-bias operation.	1 max.	megohm

^a Pin is cut off close to ceramic wafer.→ ^b For operation at metal-shell temperatures up to 150° C.

→ CHARACTERISTICS RANGE VALUES FOR EQUIPMENT DESIGN

	Note	Min.	Max.	
Heater Current.	1	0.125	0.145	amp
Direct Interelectrode Capacitances:				
Grid to plate	2	1.8	2.6	μf
Grid to cathode, shell, and heater.	2	3.8	4.6	μf
Plate to cathode, shell, and heater.	2	1.4	1.8	μf
Heater to cathode	2	1.1	1.7	μf
Plate to cathode.	2	0.2	0.32	μf
Plate Current (1)	1,3	9	12.5	ma
Plate Current (2)	1,4	-	50	μa
Transconductance (1).	1,3	10000	13000	μmhos
Transconductance (2).	3,5	9000	-	μmhos
Transconductance Change:				
Difference between Transconductance (1) and Transconductance (2), expressed in per cent of Transconductance (1)	-	-	15	%
Reverse Grid Current.	1,6	-	0.1	μa
Amplification Factor.	1,3	28	40	
Heater-Cathode Leakage Current:				
Heater negative with respect to cathode.	1,7	-	5	μa
Heater positive with respect to cathode.	1,7	-	5	μa

→ Indicates a change.



Leakage Resistance:

Between grid and all other electrodes tied together.	1,8	1000	-	megohms
Between plate and all other electrodes tied together.	1,9	1000	-	megohms

Note 1: With 6.3 volts ac or dc on heater.

Note 2: Measured in accordance with EIA Standard RS-191-A.

Note 3: With dc plate supply volts = 75, cathode resistor = 100 ohms, and cathode-bypass capacitor = 1000 μ f.

Note 4: With dc plate volts = 75, dc grid volts = -7, and metal shell connected to ground.

Note 5: With 5.7 volts ac or dc on heater.

Note 6: With dc plate volts = 80, grid supply volts = -1.2, grid resistor = 0.5 megohm, and metal shell connected to ground.

Note 7: With 100 volts dc applied between heater and cathode.

Note 8: With grid 100 volts negative with respect to all other electrodes tied together.

Note 9: With plate 300 volts negative with respect to all other electrodes tied together.

SPECIAL RATINGS & PERFORMANCE DATA**Shock Rating:**

Impact Acceleration 1000 max. g

This test is performed on a sample lot of tubes from each production run to determine ability of tube to withstand the specified impact acceleration. Tubes are held rigid in four different positions in a Navy Type, High-impact (flyweight) Shock Machine and are subjected to 20 blows at the specified maximum impact acceleration. At the end of this test, tubes are criticized for change in transconductance, reverse grid current, and heater-cathode leakage current, and are then subjected to the Variable-Frequency Vibration Test described below.

Fatigue Rating:

Vibrational Acceleration. 2.5 max. g

This test is performed on a sample lot of tubes to determine ability of tube to withstand the specified vibrational acceleration. Tubes are rigidly mounted, supplied with nominal heater voltage only, and subjected for 48 hours to 2.5-g vibrational acceleration at 60 cycles per second in the X₁ position. At the end of this test, tubes are criticized for the same characteristics and end-point values as in the Shock Rating Test described above.

Variable-Frequency Vibration Performance:

This test is performed on a sample lot of tubes from each production run. The tube is operated under the conditions specified in CHARACTERISTICS RANGE VALUES for Transconductance (I) with the addition of a plate-load resistor of 2000 ohms. During operation, tube is vibrated in a direction perpendicular to the longitudinal axis of the tube through the frequency range from 50 to 15,000 cycles per second under the following

← Indicates a change.



conditions: a sweep rate of one octave per 30 seconds from 50 to 3000 cps, a 7-second sweep from 3000 to 15,000 cps, and a constant vibrational acceleration of 1 g. During the test, tube must not show an rms output voltage across the plate-load resistor in excess of: (1) 25 millivolts from 50 to 6000 cps, and (2) 500 millivolts from 6000 to 15,000 cps.

Low-Pressure Voltage-Breakdown Test:

This test is performed on a sample lot of tubes from each production run. In this test, tubes are operated with 240 rms volts applied between plate and all other electrodes and will not break down or show evidence of corona when subjected to air pressures equivalent to altitudes of up to 100,000 feet.

→ Heater Cycling:

Cycles of Intermittent Operation. . . . 2000 min. cycles

This test is performed on a sample lot of tubes from each production run under the following conditions: heater volts = 7.5 cycled one minute on and two minutes off; heater 100 volts negative with respect to cathode; grid, plate, and metal shell connected to ground. At the end of this test, tubes are tested for open heaters and heater-cathode shorts.

→ Shorts and Continuity:

This test is performed on a sample lot of tubes from each production run. Tubes are subjected to the Thyatron-Type Shorts Test described in MIL-E-1D, Amendment 2, Paragraph 4.7.7, except that tapping is done by hand with a soft rubber tapper^c. See accompanying Shorts-Test Acceptance-Limits curve. Tubes are criticized for permanent or temporary shorts and open circuits.

Early-Hour Stability Life Performance:

This test is performed on a sample lot of tubes from each production run to insure that tubes are properly stabilized. In this test, tubes are operated for 20 hours at maximum-rated plate dissipation. After 2 hours of operation and again after 20 hours of operation, tubes are checked for transconductance under the conditions specified in CHARACTERISTICS RANGE VALUES for Transconductance (1). A tube is rejected if its transconductance after 2 or 20 hours of operation has changed more than 10 per cent from the 0-hour value.

100-Hour Life Performance:

This test is performed on a sample lot of tubes from each production run to insure a low percentage of early-hour inoperatives. Tubes are operated for 100 hours at maximum-rated plate dissipation, and then subjected to the Shorts and Continuity Test previously described. Tubes must then show a transconductance of not less than 7500 micromhos under the conditions specified in CHARACTERISTICS RANGE VALUES for Transconductance (1).

→ Indicates a change.



1000-Hour Conduction Life Performance:

This test is performed on a sample lot of tubes from each production run to insure high quality of the individual tube and guard against epidemic failures due to excessive changes in any of the characteristics indicated below. In this test, tubes are operated for 1000 hours at maximum-rated plate dissipation^d, and then criticized for inoperatives, reverse grid current, heater-cathode leakage current, and leakage resistance. In addition, the average change in transconductance of the lot from the 0-hour value for Transconductance (1) specified in CHARACTERISTICS RANGE VALUES, must not exceed 15 per cent at 500 hours, and 20 per cent at 1000 hours.



1000-Hour Standby Life Performance:

This test is performed on a sample lot of tubes from each production run. The tubes are operated for 1000 hours with only heater voltage applied. Tubes are criticized for inter-electrode leakage, reverse grid current, change in transconductance of individual tubes from values at 0-hours and cathode interface resistance greater than 25 ohms. Interface resistance is measured by Method B of ASTM specification F300-57T.

^c Specifications for taper supplied on request.

^d At shell temperature of 150° C.






92CS-10970R1

NOTE 1: MAXIMUM OUTSIDE DIAMETER OF 0.440" IS PERMITTED ALONG 0.190" LUG LENGTH.

NOTE 2: SHELL TEMPERATURE SHOULD BE MEASURED IN ZONE "A" BETWEEN BROKEN LINES.


AVERAGE PLATE CHARACTERISTICS



92CM-10460RI




AVERAGE CHARACTERISTICS



92CM-10464RI




AVERAGE CHARACTERISTICS



92CM-10964




AVERAGE CHARACTERISTICS



92CS-10461R1

SHORTS-TEST ACCEPTANCE LIMITS



92CS-10465