

## TUNG-SOL

## DOUBLE DIODE TRIODE

MINIATURE TYPE


COATED UNIPOTENTIAL CATHODE

HEATER


6.3 VOLTS 0.3 AMP.

AC OR DC

ANY MOUNTING POSITION



GLASS BULB


**BOTTOM VIEW**  
 MINIATURE BUTTON  
 7 PIN BASE

7BT

THE 6AT6 IS A COMBINED HIGH-MU VOLTAGE AMPLIFIER AND DOUBLE-DIODE DETECTOR USING THE 7 PIN MINIATURE CONSTRUCTION. IT IS INTENDED TO PROVIDE OUTPUT VOLTAGE ADEQUATE FOR FULL POWER OUTPUT OF MOST BEAM POWER TUBES.

## DIRECT INTERELECTRODE CAPACITANCES

	WITH SHIELD <sup>A</sup>	WITHOUT SHIELD	
GRID TO PLATE: (G TO TRIODE PLATE)	2.0	2.0	$\mu\mu f$
INPUT: G TO (H+K)	2.2	2.2	$\mu\mu f$
OUTPUT: P TO (H+K)	1.2	0.8	$\mu\mu f$
COUPLING: #2 DIODE PLATE TO GRID (MAX.)	0.04	0.04	$\mu\mu f$
COUPLING: #1 DIODE PLATE TO GRID (MAX.)*		0.07	$\mu\mu f$
#2 DIODE PLATE TO HEATER AND CATHODE *		0.95	$\mu\mu f$
#1 DIODE PLATE TO HEATER AND CATHODE *		0.66	$\mu\mu f$

<sup>A</sup> EXTERNAL SHIELD #316 CONNECTED TO CATHODE.

## RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

HEATER VOLTAGE	6.3	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE	90	VOLTS
MAXIMUM PLATE VOLTAGE	300	VOLTS
MAXIMUM PLATE DISSIPATION	0.5	WATT
MAXIMUM POSITIVE DC GRID #1 VOLTAGE	0	VOLTS
MAXIMUM DIODE CURRENT (EACH UNIT) FOR CONTINUOUS OPERATION	1.0	MA.

\*INDICATES AN ADDITION.

CONTINUED ON FOLLOWING PAGE

## TUNG-SOL

CONTINUED FROM PRECEDING PAGE

## TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A<sub>1</sub> AMPLIFIER

HEATER VOLTAGE	6.3	6.3	VOLTS
HEATER CURRENT	0.3	0.3	AMP.
PLATE VOLTAGE	100	250	VOLTS
GRID #1 VOLTAGE	-1	-3	VOLTS
PLATE RESISTANCE	54 000	58 000	OHMS
AMPLIFICATION FACTOR	70	70	
TRANSCONDUCTANCE	1 300	1 200	UMHOS
PLATE CURRENT	0.8	1.0	MA.
AVERAGE DIODE CURRENT (EACH UNIT) AT 10 VOLTS DC	2.0	2.0	MA.

## RESISTANCE COUPLED AMPLIFIER

## TRIODE UNIT

HEATER VOLTAGE	6.3	6.3	VOLTS
PLATE SUPPLY VOLTAGE	90	250	VOLTS
CONTROL VOLTAGE	0	0	VOLTS
PLATE LOAD RESISTOR	220 000	470 000	OHMS
CONTROL GRID RESISTOR	10.0	10.0	MEGOHMS
INPUT CONDENSER	0.01	0.01	μf
OUTPUT CONDENSER	0.01	0.01	μf
GRID RESISTOR OF FOLLOWING STAGE	470 000	470 000	OHMS
SIGNAL SOURCE IMPEDANCE (MAX.)	1 000	1 000	OHMS
DISTORTION	5	5	PERCENT
OUTPUT VOLTAGE	8	34	VOLTS
VOLTAGE GAIN AT 400 CPS.	35	46	