

# 3AU6

## Sharp-Cutoff Pentode

### 7-PIN MINIATURE TYPE

The 3AU6 is the same as the 6AU6A except for:

#### Heater Characteristics and Ratings:

Current . . . . .	0.600 ± 0.040	A
Voltage (AC or DC) at heater amperes = 0.600 . . . . .	3.15	V
Warm-up time (Average) . . . . .	11	s

# 3AV6

## Twin Diode-High-Mu Triode

### 7-PIN MINIATURE TYPE

The 3AV6 is the same as the 6AV6 except for:

#### Heater Characteristics and Ratings:

Current . . . . .	0.600 ± 0.040	A
Voltage (AC or DC) at heater amperes = 0.600 . . . . .	3.15	V
Warm-up time (Average) . . . . .	11	s

# 3BA6

## Remote-Cutoff Pentode

The 3BA6 is the same as the 6BA6 except for:

#### Heater Characteristics and Ratings:

Current . . . . .	0.600 ± 0.040	A
Voltage (ac or dc) at 0.600 A . . . . .	3.15	V
Warm-up Time (Average) . . . . .	11	s

# 3BN4A

## Medium-Mu Triode

The 3BN4A is the same as the 6BN4A except for:

#### Heater Characteristics and Ratings:

Current . . . . .	0.450 ± 0.030	A
Voltage (ac or dc) at 0.450 A . . . . .	3	V
Warm-up Time (Average) . . . . .	11	s