



6AF3

HALF-WAVE VACUUM RECTIFIER

9-PIN MINIATURE TYPE

For television damper service

6AF3

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC) 6.3 ± 10% volts

Current 1.2 amp

Direct Interelectrode Capacitances (Approx.):^o

Plate to cathode and heater 6 μf

Cathode to plate and heater 9 μf

Heater to cathode 2.8 μf

Mechanical:

Operating Position Any

Maximum Overall Length 3-9/32"

Maximum Seated Length 2-7/8" ± 1/8"

Diameter 0.750" to 0.875"

Dimensional Outline See General Section


Bulb T6-1/2

Cap Skirted Miniature (JEDEC No. C1-2)

Base Small-Button Noval 9-Pin (JEDEC No. E9-1)

Basing Designation for BOTTOM VIEW 9CB

- Pin 1 - Internal Connection— Do Not Use[♦]
- Pin 2 - Same as Pin 1
- Pin 3 - Same as Pin 1
- Pin 4 - Heater



- Pin 5 - Heater
- Pin 6 - Same as Pin 1
- Pin 7 - Same as Pin 1
- Pin 8 - Same as Pin 1
- Pin 9 - Plate
- Cap - Cathode

DAMPER SERVICE

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system[□]

PEAK INVERSE PLATE VOLTAGE 4500[■] max. volts

PEAK PLATE CURRENT 750 max. ma

DC PLATE CURRENT 185 max. ma

PLATE DISSIPATION 6 max. watts

PEAK HEATER CATHODE VOLTAGE:

Heater negative with respect to cathode . 4500^{*} max. volts

Heater positive with respect to cathode . 300[▲] max. volts

BULB TEMPERATURE (At hottest point on bulb surface) 210 max. °C

Characteristics:

Tube-Voltage Drop for plate ma. = 340 . . . 30 volts

^o Without external shield.

[♦] Socket terminals 1, 2, 3, 6, 7, and 8 should not be used as tie points.

[□] As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

6AF3



6AF3

HALF-WAVE VACUUM RECTIFIER

■ This rating is applicable where the duty cycle of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

* The dc component must not exceed 1000 volts.

▲ The dc component must not exceed 100 volts.